

Boston Scientific Corporation

CONFIDENTIAL



**Phillips Sumika**  
Polypropylene Company

## Material Safety Data Sheet

### SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

## MARLEX® POLYPROPYLENES (ALL GRADES)

Product Use: Coatings  
Synonyms: PLASTIC  
Product Cas No.: MIXTURE

Company Identification:  
Chevron Phillips Chemical Company LP  
10001 Six Pines Drive  
The Woodlands, TX 77380

Product Information:  
MSDS Requests: (800) 852-5530  
Technical Information: (800) 852-5531

#### 24-Hour Emergency Telephone Numbers

HEALTH :CT Emergency Information Center (800) 231-0623 or (510) 231-0625  
TRANSPORTATION : North America: CHEMTREC (800) 424-9300 or (703) 527-3887  
ASIA: (800) ALERTSGS or (800) 25378747 or +65+6542+9595  
EUROPE: BIG +32+14+584545 (phone) or +32+14+583516 (telefax)  
SOUTH AMERICA SOS-Cotec Inside Brazil: 0800+111+767  
Outside Brazil: 55+19+3487+1800

**MEDICAL APPLICATION CAUTION:** Do not use this Chevron Phillips Chemical Company LP material in medical applications involving permanent implantation in the human body or permanent contact with internal body fluids or tissues.

Do not use this Chevron Phillips Chemical Company LP material in medical applications involving brief or temporary implantation in the human body or contact with internal body fluids or tissues unless the material has been provided directly from Chevron Phillips Chemical Company LP under an agreement which expressly acknowledges the contemplated use.

Chevron Phillips Chemical Company LP makes no representation, promise, express warranty or implied warranty concerning the suitability of this material for use in implantation in the human body or in contact with internal body fluids or tissues.

### SECTION 2 COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENT	CAS NUMBER	AMOUNT	EINECS	SYM	R-PHRASES
-----------	------------	--------	--------	-----	-----------

Revision Number: 3  
Revision Date: 01/28/2004

1 of 9

MARLEX® POLYPROPYLENES (ALL GRADES)  
MSDS : 240560

Abbreviated 510(k)  
Pinnacle™ Pelvic Floor Repair Kits  
July 12, 2007

Page 38 of 149

**EXHIBIT**

**10**

CONFIDENTIAL  
BSCM04500000465

Boston Scientific Corporation

CONFIDENTIAL

PROPYLENE ETHYLENE COPOLYMER	9003-07-0	50 - 99 % weight	NA	NA	NA
POLYPROPYLENE	9003-07-0	50 - 99 % weight	NA	NA	NA
POLYETHYLENE	9002-88-4	< 49 % weight	EXEMPT	NA	NA
POLYETHYLENE HEXENE COPOLYMER	25213-02-9	< 49 % weight	NA	NA	NA
ETHYLENE-OCTENE-1COPOLYMER	26221-73-8	< 49 % weight	NA	NA	NA
POLYETHYLENE BUTENE COPOLYMER	25087-34-7	< 49 % weight	NA	NA	NA
RELATED MATERIALS	VARIOUS	< 4 % weight	NA	NA	NA

**Occupational Exposure Limits:**

Component	Limit	TWA	STEL / Peak	Ceiling	Notation
PROPYLENE ETHYLENE COPOLYMER	CPCHEM	Not Established	NA	NA	NA
POLYPROPYLENE	CPCHEM	Not Established	NA	NA	NA
POLYETHYLENE	CPCHEM	Not Established	NA	NA	NA
POLYETHYLENE HEXENE COPOLYMER	CPCHEM	Not Established	NA	NA	NA
ETHYLENE-OCTENE-1COPOLYMER	CPCHEM	Not Established	NA	NA	NA
POLYETHYLENE BUTENE COPOLYMER	CPCHEM	Not Established	NA	NA	NA

Control as Particulate Not Otherwise Classified (PNOC). The ACGIH Guideline\* for respirable dust is 3.0 mg/m<sup>3</sup> and 10.0 mg/m<sup>3</sup> for total dust. The OSHA PEL for respirable dust is 5.0 mg/m<sup>3</sup> and 15.0 mg/m<sup>3</sup> for total dust.

\* This value is for inhalable (total) particulate matter containing no asbestos and < 1.0% crystalline silica.

**SECTION 3 HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

Opaque, translucent waxy pellets or fluff, mild odor.

- FORMALDEHYDE MAY BE PRODUCED AT ELEVATED TEMPERATURE.
- DUST MAY PRODUCE MECHANICAL IRRITATION TO THE MUCOUS MEMBRANES OF THE EYES, NOSE, THROAT AND UPPER RESPIRATORY TRACT

**IMMEDIATE HEALTH EFFECTS:**

**Eye:** Contact with the eyes may cause irritation due to the abrasive action of the dust. Not expected to cause prolonged or significant eye irritation. Material is dusty and may scratch the surface of the eye.

**Skin:** Not expected to be harmful to internal organs if absorbed through the skin. Contact with the skin is not expected to cause prolonged or significant irritation.

**Ingestion:** Not expected to be harmful if swallowed.

**Inhalation:** Not expected to be harmful if inhaled. The dust from this material may cause respiratory irritation.

**SECTION 4 FIRST AID MEASURES**

Revision Number: 3  
Revision Date: 01/26/2004

2 of 9

MARLEX® POLYPROPYLENES (ALL GRADES)  
MSDS : 240590



Boston Scientific Corporation

CONFIDENTIAL

**Eye:** Flush eyes with water immediately while holding the eyelids open. Remove contact lenses, if worn, after initial flushing, and continue flushing for at least 15 minutes. Get medical attention if irritation persists.

**Skin:** If the hot material gets on skin, quickly cool in water. See a doctor for extensive burns. Remove contaminated clothing and shoes. Wash skin with soap and water. Wash or clean contaminated clothing and shoes before reuse.

**Ingestion:** If swallowed, do not induce vomiting. Give the person a glass of water or milk to drink and get immediate medical attention. Never give anything by mouth to an unconscious person.

**Inhalation:** Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if breathing difficulties continue.

#### SECTION 5 FIRE FIGHTING MEASURES

Explosive dust clouds may be produced.

##### FIRE CLASSIFICATION:

OSHA Classification (29 CFR 1910.1200): Not classified by OSHA as flammable or combustible.

NFPA RATINGS: Health: 1 Flammability: 1 Reactivity: 0

##### FLAMMABLE PROPERTIES:

Flashpoint: 343°C (649.4°F)

Autoignition: N/A

Flammability (Explosive) Limits (% by volume in air): Lower: NA Upper: NA

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

##### PROTECTION OF FIRE FIGHTERS:

**Fire Fighting Instructions:** This material will burn although it is not easily ignited. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus. If possible, water should be applied as a spray from a fogging nozzle since this is a surface burning material. The application of high velocity water will spread the burning surface layer.

**Combustion Products:** Incomplete combustion can also produce formaldehyde. Normal combustion forms carbon dioxide, water vapor and may produce carbon monoxide, original monomer, other hydrocarbons and hydrocarbon oxidation products, depending on temperature and air availability. Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

#### SECTION 6 ACCIDENTAL RELEASE MEASURES

**Protective Measures:** Eliminate all sources of ignition in vicinity of spilled material.

**Spill Management:** Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Avoid creating dust clouds. Shovel, sweep up or use industrial vacuum cleaner to pick up. Place in container for proper disposal. Reduce airborne dust and prevent scattering by moistening with water.

**Reporting:** U.S.A. regulations require reporting spills of this material that could reach any surface waters. Report spills to local authorities and/or the U.S. Coast Guard National Response Center

Revision Number: 3  
Revision Date: 01/26/2004

3 of 9

MARLEX® POLYPROPYLENES (ALL GRADES)  
MSDS : 240590



Boston Scientific Corporation

CONFIDENTIAL

at (800) 424-8802 as appropriate or required.

## SECTION 7 HANDLING AND STORAGE

READ AND OBSERVE ALL PRECAUTIONS ON PRODUCT LABEL. REFER TO PRODUCT LABEL OR MANUFACTURERS TECHNICAL BULLETINS FOR THE PROPER USE AND HANDLING OF THIS MATERIAL.

**Precautionary Measures:** Use caution to avoid creation of dusts and to prevent inhalation of product dust (fines). Avoid contact with product dust. Airborne dust concentrations above 20 mg/l may create a dust explosion hazard. Keep out of water sources and sewers. Spilled pellets may create a slipping hazard. Avoid breathing vapors or fumes which may be released during thermal processing. Do not breathe dust at levels above the recommended exposure limits. Avoid breathing material. Keep container closed. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Discard contaminated clothing and shoes or thoroughly clean before reuse. Do not breathe dust. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

**Unusual Handling Hazards:** At extrusion temperatures (>350F, >177C), polyethylenes can release vapors and gases, which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. These substances may include acetaldehyde, acetone, acetic acid, formic acid, formaldehyde and acrolein. Based on animal data and limited epidemiological evidence, NTP, IARC (2A), and OSHA have listed formaldehyde as a probable human carcinogen. Following all recommendations within this MSDS should minimize exposure to thermal processing emissions.

**Static Hazard:** Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations, which have the potential of generating an accumulation of electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids, National Fire Protection Association (NFPA 77), 'Recommended Practice on Static Electricity' (liquids, powders and dusts), and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents' (liquids).

**General Storage Information:** Treat as a solid that can burn. Store away from oxidizing materials, in a cool, dry place with adequate ventilation. Bond and ground transfer equipment. DO NOT USE OR STORE near heat, sparks or open flames. USE AND STORE ONLY IN WELL VENTILATED AREA. Keep container closed when not in use.

**Container Warnings:** Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Containers, even those that have been emptied, can contain residues of dusts or solid particulates which may create both health and fire/explosion hazards.

## SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 3), applicable exposure limits, job

Revision Number: 3  
Revision Date: 01/25/2004

4 of 9

MARLEX® POLYPROPYLENES (ALL GRADES)  
MSDS : 240590



## Boston Scientific Corporation

CONFIDENTIAL

activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**ENGINEERING CONTROLS:**

If handling results in dust generation, special ventilation may be needed to ensure that dust exposure does not exceed the OSHA PEL for nuisance dust. Use in a well-ventilated area. If heated material generates vapor or fumes, use process enclosures, local exhaust ventilation, or other engineering controls to control exposure.

**PERSONAL PROTECTIVE EQUIPMENT:**

**Eye/Face Protection:** No special eye protection is normally required. If operating conditions create dust that is not adequately controlled, wear chemical goggles.

**Skin Protection:** No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

**Respiratory Protection:** No respiratory protection is normally required. If heated material generates vapor or fumes that are not adequately controlled by ventilation, wear a NIOSH approved respirator. Use the following elements for air-purifying respirators: Organic Vapor and Formaldehyde.

Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

**Occupational Exposure Limits:**

Component	Limit	TWA	STEL / Peak	Ceiling	Notation
PROPYLENE ETHYLENE COPOLYMER	CPCHEM	Not Established	NA	NA	NA
POLYPROPYLENE	CPCHEM	Not Established	NA	NA	NA
POLYETHYLENE	CPCHEM	Not Established	NA	NA	NA
POLYETHYLENE HEXENE COPOLYMER	CPCHEM	Not Established	NA	NA	NA
ETHYLENE-OCTENE-1COPOLYMER	CPCHEM	Not Established	NA	NA	NA
POLYETHYLENE BUTENE COPOLYMER	CPCHEM	Not Established	NA	NA	NA

Control as Particulate Not Otherwise Classified (PNOC). The ACGIH Guideline\* for respirable dust is 3.0 mg/m<sup>3</sup> and 10.0 mg/m<sup>3</sup> for total dust. The OSHA PEL for respirable dust is 5.0 mg/m<sup>3</sup> and 15.0 mg/m<sup>3</sup> for total dust.

\* This value is for inhalable (total) particulate matter containing no asbestos and < 1.0% crystalline silica.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE AND ODOR:** Opaque, translucent waxy pellets or fluff, mild odor.

**pH:** NA

**VAPOR PRESSURE:** NA

**VAPOR DENSITY (AIR=1):** NA

Revision Number: 3  
Revision Date: 01/28/2004

5 of 9

MARLEX® POLYPROPYLENES (ALL GRADES)  
MSDS : 240590

Boston Scientific Corporation

CONFIDENTIAL

**BOILING POINT:** NA  
**SOLUBILITY (in water) :** Negligible  
**SPECIFIC GRAVITY:** 0.88 g/cm<sup>3</sup> - 0.92 g/cm<sup>3</sup>

#### SECTION 10. STABILITY AND REACTIVITY

**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.  
**Conditions to Avoid:** Not Applicable  
**Incompatibility With Other Materials:** May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.  
**Hazardous Decomposition Products:** Low molecular weight hydrocarbons, alcohols, aldehydes, acids and ketones can be formed during thermal processing.  
**Hazardous Polymerization:** Hazardous polymerization will not occur.

#### SECTION 11. TOXICOLOGICAL INFORMATION

##### IMMEDIATE HEALTH EFFECTS:

**Acute Oral Toxicity:** The oral LD50 is not known.  
**Acute Dermal Toxicity:** The dermal LD50 is not known.  
**Acute Inhalation Toxicity:** The inhalation LC50 is not known.

**Eye Irritation:** This material is not expected to be irritating to the eyes.  
**Skin Irritation:** This material is not expected to be irritating to the skin.

##### ADDITIONAL TOXICOLOGY INFORMATION:

Long term exposure to high dust concentrations may cause non-debilitating lung changes.

This product contains POLYMERIZED ETHYLENE.

At extrusion temperatures (>350F, >177C), polyethylenes can release vapors and gases, which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. These substances may include acetaldehyde, acetone, acetic acid, formic acid, formaldehyde and acrolein. Generally these irritant effects are all transitory. However, prolonged exposure to irritating off gases can lead to pulmonary edema. Adequate ventilation should prevent sensory discomfort. Based on animal data and limited epidemiological evidence, NTP, IARC (2A), and OSHA have listed formaldehyde as a probable human carcinogen. Following all recommendations within this MSDS should minimize exposure to thermal processing emissions. Long-term exposure to high dust concentrations may cause non-debilitating lung changes.

#### SECTION 12. ECOLOGICAL INFORMATION

##### ECOTOXICITY:

Fish or birds may eat pellets which may obstruct their digestive tracts.

##### ENVIRONMENTAL FATE:

This material is not expected to be readily biodegradable.

Revision Number: 3  
 Revision Date: 01/28/2004

6 of 9

MARLEX® POLYPROPYLENES (ALL  
 GRADES)  
 MSDS : 240590



Boston Scientific Corporation

CONFIDENTIAL

**SECTION 13 DISPOSAL CONSIDERATIONS**

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

**SECTION 14 TRANSPORT INFORMATION**

The description shown may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

Shipping Descriptions per regulatory authority.

**US DOT**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION

**ICAO / IATA**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION

**IMO / IMDG**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION

**RID / ADR**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION

**SECTION 15 REGULATORY INFORMATION****SARA 311/312 CATEGORIES:**

- |                                       |     |
|---------------------------------------|-----|
| 1. Immediate (Acute) Health Effects:  | YES |
| 2. Delayed (Chronic) Health Effects:  | NO  |
| 3. Fire Hazard:                       | NO  |
| 4. Sudden Release of Pressure Hazard: | NO  |
| 5. Reactivity Hazard:                 | NO  |

**REGULATORY LISTS SEARCHED:**

- |                             |                             |                             |
|-----------------------------|-----------------------------|-----------------------------|
| 04A = IARC Group 1          | 12 = TSCA Section 8(a) PAIR | 21 = TSCA Section 5(a)      |
| 04B = IARC Group 2A         | 13 = TSCA Section 8(d)      | 25 = CAA Section 112 HAPs   |
| 04C = IARC Group 2B         | 15 = SARA Section 313       | 26 = CWA Section 311        |
| 05 = NTP Carcinogen         | 16 = CA Proposition 65      | 28 = CWA Section 307        |
| 06 = OSHA Carcinogen        | 17 = MA RTK                 | 30 = RCRA Waste P-List      |
| 08 = TSCA 12(b)             | 18 = NJ RTK                 | 31 = RCRA Waste U-List      |
| 10 = TSCA Section 4         | 19 = DOT Marine Pollutant   | 32 = RCRA Appendix VIII     |
| 11 = TSCA Section 8(a) CAIR | 20 = PA RTK                 | 33 = MN Hazardous Substance |

No components of this material were found on the regulatory lists above.

Revision Number: 3  
Revision Date: 01/26/2004

7 of 9

MARLEX® POLYPROPYLENES (ALL GRADES)  
MSDS : 240590

Boston Scientific Corporation

CONFIDENTIAL

**WHMIS CLASSIFICATION:**

This product is not considered a controlled product according to the criteria of the Canadian Controlled Products Regulations.

**CHEMICAL INVENTORY LISTINGS:**

AUSTRALIA: This material contains components that require notification before sale or importation into Australia.

CANADA: This material contains components that are neither on the Domestic Substance List (DSL) nor on the Non-domestic Substances List (NDSL).

PEOPLE'S REPUBLIC OF CHINA: All the components of this product are listed on the draft inventory of Existing Chemical Substances in China.

JAPAN: This material contains components that require notification before sale or importation into Japan.

KOREA: All the components of this product are on the Existing Chemicals List (ECL) in Korea.

PHILIPPINES: This material contains components that require notification before sale or importation into the Philippines.

UNITED STATES: All of the components of this material are on the Toxic Substances Control Act (TSCA) Chemical Inventory.

**EU RISK AND SAFETY PHRASES:**

S22: Do not breathe dust.

EU Symbols: NA

**SECTION 16 OTHER INFORMATION**

**NEPA RATINGS:** Health: 1 Flammability: 1 Reactivity: 0 Special: NA

(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE - Personal Protection Equipment Index recommendation, \* - Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA).

**REVISION STATEMENT:** This revision affects all sections please review.

**ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:**

TLV	Threshold Limit Value	TWA	- Time Weighted Average
STEL	Short-term Exposure Limit	PEL	- Permissible Exposure Limit
ACGIH	American Conference of - Government Industrial Hygienists	OSHA	- Occupational Safety & Health
NIOSH	National Institute of Safety & Health	NFPA	- National Fire Protection Agency
WHMIS	Workplace Hazardous Materials - Information System	IRAC	- Intl. Agency for Research on Cancer
EINECS	European Inventory of existing - Commercial Chemical Sales	RCRA	- Resource Conservation Recovery Act

Revision Number: 3  
Revision Date: 01/28/2004

5 of 9

MARLEX® POLYPROPYLENES (ALL  
GRADES)  
MSDS : 240590



Boston Scientific Corporation

CONFIDENTIAL

SARA	- Superfund Amendments and Reauthorization Act.	TSCA	- Toxic Substance Control Act
EC50	- Effective Dose	LC50	- Lethal Concentration
LD50	- Lethal Dose	CAS	- Chemical Abstract Service Number
NDA	- No Data Available	NA	- Not Applicable
<=	- Less Than or Equal To	>=	- Greater Than or Equal To
CNS	- Central Nervous System	MAK	- Germany Maximum Concentration Values

Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the ANSI MSDS Standard (Z400.1) by EHS Product Stewardship Group, Chevron Phillips Chemical Company LP, 10001 Six Pines Drive, The Woodlands, TX 77380

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

Revision Number: 3  
Revision Date: 01/28/2004


9 of 9

MARLEX® POLYPROPYLENES (ALL GRADES)  
MSDS : 240590

Abbreviated 510(k)  
Pinnacle™ Pelvic Floor Repair Kits  
July 12, 2007

Page 46 of 149

CONFIDENTIAL  
BSCM04500000473



**Phillips Sumika**  
Polypropylene Company

# Material Safety Data Sheet

## SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

### Marlex® Polypropylene (All Grades)

**Product Use:** Extrusion and Injection Molding

**Synonyms:** Plastic

**Product CAS No.:** Mixture

**Company Identification:**

Phillips Sumika Polypropylene Company  
10001 Six Pines Drive  
The Woodlands, TX 77380

**Product Information:**

MSDS Requests: 1 - (800) 852-5530  
Technical Information: 1 - (800) 852-5531  
Responsible Party: Product Safety Group  
Email:msds@cpchem.com

Chevron Phillips Chemicals International N.V.  
Brusselsesteenweg 355  
B-3090 Overijse  
Belgium

**24-Hour Emergency Telephone Numbers**

HEALTH:Chevron Phillips Emergency Information Center 866.442.9628 (North America) and 1.832.813.4984 (International)

TRANSPORTATION: North America: CHEMTREC 800.424.9300 or 703.527.3887  
ASIA: +1.703.527.3887  
EUROPE: BIG .32.14.584545 (phone) or .32.14.583516 (telefax)  
SOUTH AMERICA SOS-Cotec Inside Brazil: 0800.111.767  
Outside Brazil: 55.19.3467.1600

**MEDICAL APPLICATION CAUTION:** Do not use this Phillips Sumika Polypropylene Company material in medical applications involving permanent implantation in the human body or permanent contact with internal body fluids or tissues.

Do not use this Phillips Sumika Polypropylene Company material in medical applications involving brief or temporary implantation in the human body or contact with internal body fluids or tissues unless the material has been provided directly from Phillips Sumika Polypropylene Company under an agreement which expressly acknowledges the contemplated use.

Phillips Sumika Polypropylene Company makes no representation, promise, express warranty or implied warranty concerning the suitability of this material for use in implantation in the human body or in contact with internal body fluids or tissues.

**Revision Number:** 5.02  
**Revision Date:** 02/13/2008

1 of  
##NUMPAGES##

**Marlex® Polypropylene (All Grades)**  
**MSDS :** 240590



**SECTION 2 HAZARDS IDENTIFICATION**

\*\*\*\*\*

**EMERGENCY OVERVIEW**

Opaque, translucent waxy pellets or fluff, mild odor.

**NFPA RATINGS:**      **Health:** 1      **Flammability:** 1      **Reactivity:** 0**Signal Word:**

NA - Not Applicable    Warning

**Safety Phrases:**

S22: Do not breathe dust.

\*\*\*\*\*

**IMMEDIATE HEALTH EFFECTS:****Eye:** Contact with the eyes may cause irritation due to the abrasive action of the dust. Not expected to cause prolonged or significant eye irritation. Material is dusty and may scratch the surface of the eye.**Skin:** Contact with the skin is not expected to cause prolonged or significant irritation.**Ingestion:** Not expected to be harmful if swallowed.**Inhalation:** Not expected to be harmful if inhaled.**SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS**

COMPONENT	CAS NUMBER	AMOUNT	EINECS	SYM	R-PHRASES
Propylene Ethylene Copolymer	9010-79-1	50 - 99 % weight	NA	NA	NA
Polypropylene	9003-07-0	50 - 99 % weight	NA	NA	NA
Polyethylene	9002-88-4	< 49 % weight	EXEMPT	NA	NA
Polyethylene Hexene Copolymer	25213-02-9	< 49 % weight	EXEMPT	NA	NA
Ethylene-octene-1 Copolymer	26221-73-8	< 49 % weight	NA	NA	NA
Polyethylene Butene Copolymer	25087-34-7	< 49 % weight	NA	NA	NA
Related Materials		< 4 % weight	NA	NA	NA

**Occupational Exposure Limits:**

Component	Limit	TWA	STEL	Ceiling / Peak	Notation
Ethylene-octene-1 Copolymer	ACGIH	Not Established	NA	NA	NA
Polyethylene	ACGIH	3 mg/m3	NA	NA	NA
Polyethylene	German MAK	6 mg/m3	NA	NA	NA
Polyethylene Butene Copolymer	ACGIH	Not Established	NA	NA	NA
Polyethylene Hexene Copolymer	ACGIH	Not Established	NA	NA	NA
Polypropylene	ACGIH	3 mg/m3	NA	NA	NA
Polypropylene	German MAK	6 mg/m3	NA	NA	NA
Propylene Ethylene Copolymer	ACGIH	Not Established	NA	NA	NA
Related Materials	ACGIH	Not Established	NA	NA	NA

Control as Particulate Not Otherwise Classified (PNOC). The ACGIH Guideline\* for respirable dust is 3.0 mg/m3 and 10.0

Revision Number: 5.02  
Revision Date: 02/13/20082 of  
##NUMPAGES##Marlex® Polypropylene (All Grades)  
MSDS : 240590

mg/m<sup>3</sup> for total dust. The OSHA PEL for respirable dust is 5.0 mg/m<sup>3</sup> and 15.0 mg/m<sup>3</sup> for total dust.

\* This value is for inhalable (total) particulate matter containing no asbestos and < 1.0% crystalline silica.

#### SECTION 4 FIRST AID MEASURES

**Eye:** Flush eyes with running water immediately while holding the eyelids open. Remove contact lenses, if worn, after initial flushing, and continue flushing for at least 15 minutes. Get immediate medical attention.

**Skin:** To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse. Get medical attention if any symptoms develop. If the hot material gets on skin, quickly cool in water. See a doctor for extensive burns. Remove contaminated clothing and shoes. Wash skin with soap and water. Wash or clean contaminated clothing and shoes before reuse.

**Ingestion:** If swallowed, do not induce vomiting. Give the person a glass of water or milk to drink and get immediate medical attention. Never give anything by mouth to an unconscious person.

**Inhalation:** Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if breathing difficulties continue.

#### SECTION 5 FIRE FIGHTING MEASURES

**Explosive dust clouds may be produced.**

##### FIRE CLASSIFICATION:

OSHA Classification (29 CFR 1910.1200): Not classified by OSHA as flammable or combustible.

**NFPA RATINGS:** Health: 1 Flammability: 1 Reactivity: 0

##### FLAMMABLE PROPERTIES:

**Flashpoint:** 343°C (649.4°F)

**Autoignition:** NDA

**Flammability (Explosive) Limits (% by volume in air):** Lower: NA Upper: NA

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

##### PROTECTION OF FIRE FIGHTERS:

**Fire Fighting Instructions:** If possible, water should be applied as a spray from a fogging nozzle since this is a surface burning material. The application of high velocity water will spread the burning surface layer. This material will burn although it is not easily ignited. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

**Combustion Products:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

#### SECTION 6 ACCIDENTAL RELEASE MEASURES

**Protective Measures:** Eliminate all sources of ignition in vicinity of spilled material. Wear appropriate personal protective equipment when cleaning up spills. Refer to Section 8.

**Spill Management:** Avoid creating dust clouds. Shovel, sweep up or use industrial vacuum cleaner to pick up. Place in container for proper disposal. Reduce airborne dust and prevent scattering by moistening with water. Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

**Reporting:** U.S.A. regulations may require reporting spills of this material that could reach any surface waters. Report spills to local authorities and/or the National Response Center at (800) 424-8802 as appropriate or required.

Revision Number: 5.02  
Revision Date: 02/13/2008

3 of  
##NUMPAGES##

Marlex® Polypropylene (All Grades)  
MSDS : 240590



**SECTION 7 HANDLING AND STORAGE**

**READ AND OBSERVE ALL PRECAUTIONS ON PRODUCT LABEL . REFER TO PRODUCT LABEL OR MANUFACTURERS TECHNICAL BULLETINS FOR THE PROPER USE AND HANDLING OF THIS MATERIAL .**

**Precautionary Measures:** Use caution to avoid creation of dusts and to prevent inhalation of product dust (fines). Avoid contact with product dust. Airborne dust concentrations above 20 mg/L may create a dust explosion hazard. Keep out of water sources and sewers. Spilled pellets may create a slipping hazard. Avoid breathing vapors or fumes which may be released during thermal processing. Do not breathe dust at levels above the recommended exposure limits. Avoid breathing material. Keep container closed. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Discard contaminated clothing and shoes or thoroughly clean before reuse. Do not breathe dust. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

**Unusual Handling Hazards:** At temperatures (>350°F, >177°C), polyethylenes can release vapors and gases, which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. These substances may include acetaldehyde, acetone, acetic acid, formic acid, formaldehyde and acrolein. Based on animal data and limited epidemiological evidence, NTP, IARC (2A), and OSHA have listed formaldehyde as a probable human carcinogen. Following all recommendations within this MSDS should minimize exposure to thermal processing emissions.

**Static Hazard:** Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations, which have the potential of generating an accumulation of electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids, National Fire Protection Association (NFPA 77), Recommended Practice on Static Electricity' (liquids, powders and dusts), and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents' (liquids).

**General Storage Information:** Treat as a solid that can burn. Store away from oxidizing materials, in a cool, dry place with adequate ventilation. Bond and ground transfer equipment. DO NOT USE OR STORE near heat, sparks or open flames. USE AND STORE ONLY IN WELL VENTILATED AREA. Keep container closed when not in use.

**Container Warnings:** Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Containers, even those that have been emptied, can contain residues of dusts or solid particulates which may create both health and fire/explosion hazards.

**SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION****GENERAL CONSIDERATIONS:**

Consider the potential hazards of this material (see Section 3), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**ENGINEERING CONTROLS:**

Use in a well-ventilated area. If handling results in dust generation, special ventilation may be needed to ensure that dust exposure does not exceed the OSHA PEL for nuisance dust. If heated material generates vapor or fumes, use process enclosures, local exhaust ventilation, or other engineering controls to control exposure.

**PERSONAL PROTECTIVE EQUIPMENT:**

**Eye/Face Protection:** Wear eye protection such as safety glasses, chemical goggles, or faceshields if engineering controls or work practices are not adequate to prevent eye contact.

Revision Number: 5.02  
Revision Date: 02/13/2008

4 of  
##NUMPAGES##

Marlex® Polypropylene (All Grades)  
MSDS : 240590



**Skin Protection:** Wear impervious protective clothing to prevent skin contact. Selection of protective clothing may include gloves, apron, boots, and complete facial protection depending on operations conducted. Users should determine acceptable performance characteristics of protective clothing. Consider physical requirements and other substances present when selecting protective clothing. Suggested materials for protective gloves include: Nitrile

**Respiratory Protection:** If exposure is anticipated to be greater than applicable exposure limits, wear a NIOSH approved respirator that provides adequate protection from measured concentrations of this material. Use the following elements for air-purifying respirators: Organic Vapor and Formaldehyde.

Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

#### Occupational Exposure Limits:

Component	Limit	TWA	STEL	Ceiling / Peak	Notation
Ethylene-octene-1 Copolymer	ACGIH	Not Established	NA	NA	NA
Polyethylene	ACGIH	3 mg/m3	NA	NA	NA
Polyethylene	German MAK	6 mg/m3	NA	NA	NA
Polyethylene Butene Copolymer	ACGIH	Not Established	NA	NA	NA
Polyethylene Hexene Copolymer	ACGIH	Not Established	NA	NA	NA
Polypropylene	ACGIH	3 mg/m3	NA	NA	NA
Polypropylene	German MAK	6 mg/m3	NA	NA	NA
Propylene Ethylene Copolymer	ACGIH	Not Established	NA	NA	NA
Related Materials	ACGIH	Not Established	NA	NA	NA

Control as Particulate Not Otherwise Classified (PNOC). The ACGIH Guideline\* for respirable dust is 3.0 mg/m3 and 10.0 mg/m3 for total dust. The OSHA PEL for respirable dust is 5.0 mg/m3 and 15.0 mg/m3 for total dust.

\* This value is for inhalable (total) particulate matter containing no asbestos and < 1.0% crystalline silica.

#### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE AND ODOR:** Opaque, translucent waxy pellets or fluff, mild odor.

**pH:** NA

**Flashpoint:** 343°C (649.4°F)

**VAPOR PRESSURE:** NA

**VAPOR DENSITY (AIR=1):** NA

**BOILING POINT:** NA

**SOLUBILITY (in water):** Negligible

**SPECIFIC GRAVITY:** 0.88 g/cm3 - 0.92 g/cm3

#### SECTION 10 STABILITY AND REACTIVITY

**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Conditions to Avoid:** Not Applicable

**Incompatibility With Other Materials:** May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

**Hazardous Decomposition Products:** Low molecular weight hydrocarbons, alcohols, aldehydes, acids and ketones can be formed during thermal processing.

**Hazardous Polymerization:** Hazardous polymerization will not occur.

#### SECTION 11 TOXICOLOGICAL INFORMATION

Revision Number: 5.02  
Revision Date: 02/13/2008

5 of  
##NUMPAGES##

Marlex® Polypropylene (All Grades)  
MSDS : 240590



**IMMEDIATE HEALTH EFFECTS:****Acute Oral Toxicity:** LD50 / not known**Acute Dermal Toxicity:** LD50 / not known**Acute Inhalation Toxicity:** LC50 / not known / 4 hour(s)**Eye Irritation:** This material is not expected to be irritating to the eyes.**Skin Irritation:** This material is not expected to be irritating to the skin.**ADDITIONAL TOXICOLOGY INFORMATION:**

This product contains POLYMERIZED OLEFINS.

During thermal processing (>350°F, >177°C) polyolefins can release vapors and gases (aldehydes, ketones and organic acids) which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. Generally these irritant effects are all transitory. However, prolonged exposure to irritating off-gases can lead to pulmonary edema. Formaldehyde (an aldehyde) has been classified as a probable human carcinogen by NTP, IARC (2A), and OSHA based on animal data and limited epidemiological evidence.

Long-term exposure to high dust concentrations may cause non-debilitating lung changes.

**SECTION 12 ECOLOGICAL INFORMATION****ECOTOXICITY:**

Fish or birds may eat pellets which may obstruct their digestive tracts.

**ENVIRONMENTAL FATE:**

This material is not expected to be readily biodegradable.

**SECTION 13 DISPOSAL CONSIDERATIONS**

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

**SECTION 14 TRANSPORT INFORMATION**

The description shown may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

**Shipping Descriptions per regulatory authority.****US DOT**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION

**ICAO / IATA**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION

**IMO / IMDG**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION

Revision Number: 5.02  
Revision Date: 02/13/2008

6 of  
##NUMPAGES##

Marlex® Polypropylene (All Grades)  
MSDS : 240590

**RID / ADR**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION

**SECTION 15 REGULATORY INFORMATION****SARA 311/312 CATEGORIES:**

- |                                       |    |
|---------------------------------------|----|
| 1. Immediate (Acute) Health Effects:  | NO |
| 2. Delayed (Chronic) Health Effects:  | NO |
| 3. Fire Hazard:                       | NO |
| 4. Sudden Release of Pressure Hazard: | NO |
| 5. Reactivity Hazard:                 | NO |

**REGULATORY LISTS SEARCHED:**

01 = CA Prop 65	17 = FDA 178	33 = RCRA Waste Appendix VIII
02 = LA RTK	18 = FDA 179	34 = RCRA Waste D-List
03 = MA RTK	19 = FDA 180	35 = RCRA Waste P-List
04 = MN Hazardous Substance	20 = FDA 181	36 = RCRA Waste U-List
05 = NJ RTK	21 = FDA 182	37 = SARA Section 302
06 = PA RTK	22 = FDA 184	38 = SARA Section 313
07 = CAA Section 112 HAPs	23 = FDA 186	39 = TSCA 12 (b)
08 = CWA Section 307	24 = FDA 189	40 = TSCA Section 4
09 = CWA Section 311	25 = IARC Group 1	41 = TSCA Section 5(a)
10 = DOT Marine Pollutant	26 = IARC Group 2A	42 = TSCA Section 8(a) CAIR
11 = FDA 172	27 = IARC Group 2B	43 = TSCA Section 8(a) PAIR
12 = FDA 173	28 = IARC Group 3	44 = TSCA Section 8(d)
13 = FDA 174	29 = IARC Group 4	45 = WHIMS - IDL
14 = FDA 175	30 = NTP Carcinogen	46 = Germany D TAL
15 = FDA 176	31 = OSHA Carcinogen	47 = Germany WKG
16 = FDA 177	32 = OSHA Highly Hazardous	48 = DEA List 1
		49 = DEA List 2

The following components of this material are found on the regulatory lists indicated.

Polyethylene

4

**WHMIS CLASSIFICATION:**

This product is not considered a controlled product according to the criteria of the Canadian Controlled Products Regulations.

**CHEMICAL INVENTORY LISTINGS:**

AUSTRALIA	YES (AUS)
CANADA	YES (DSL)
CHINA	YES (IECSC)
EUROPEAN UNION	YES (EINECS)
JAPAN	YES (ENCS)
KOREA	YES (ECL)
PHILIPPINES	YES (PICCS)

Revision Number: 5.02  
Revision Date: 02/13/2008

7 of  
##NUMPAGES##

Marlex® Polypropylene (All Grades)  
MSDS : 240590



UNITED STATES

YES (TSCA)

**LABEL INFORMATION****Signal Word:**

NA - Not Applicable Warning

**Symbols:**

NA - Not Applicable

**Risk and Safety Phrases:**

S22: Do not breathe dust.

**SECTION 16 OTHER INFORMATION****NFPA RATINGS:** Health: 1 Flammability: 1 Reactivity: 0 Special: NA

(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, \*-Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA).

**REVISION STATEMENT:** The following sections have been updated: 2, 3, 8**ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:**

TLV	- Threshold Limit Value	TWA	- Time Weighted Average
STEL	- Short-term Exposure Limit	PEL	- Permissible Exposure Limit
ACGIH	- American Conference of Government Industrial Hygienists	OSHA	- Occupational Safety & Health Administration
NIOSH	- National Institute for Occupational Safety & Health	NFPA	- National Fire Protection Agency
WHMIS	- Workplace Hazardous Materials Information System	IARC	- Intl. Agency for Research on Cancer
EINECS	- European Inventory of existing Commercial Chemical Substances	RCRA	- Resource Conservation Recovery Act
SARA	- Superfund Amendments and Reauthorization Act.	TSCA	- Toxic Substance Control Act
EC50	- Effective Concentration	LC50	- Lethal Concentration
LD50	- Lethal Dose	CAS	- Chemical Abstract Service
NDA	- No Data Available	NA	- Not Applicable
<=	- Less Than or Equal To	>=	- Greater Than or Equal To
CNS	- Central Nervous System	MAK	- Germany Maximum Concentration Values

This data sheet is prepared according to the latest adaptation of the EEC Guideline 67/548.

This data sheet is prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200).

This data sheet is prepared according to the ANSI MSDS Standard (Z400.1).

This data sheet was prepared by EHS Product Stewardship Group, Chevron Phillips Chemical Company LP, 10001 Six Pines Drive, The Woodlands, TX 77380.

The above information is based on the data of which we are aware and is believed to be correct

Revision Number: 5.02  
Revision Date: 02/13/2008

8 of  
##NUMPAGES##

Marlex® Polypropylene (All Grades)  
MSDS : 240590

as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

---

Revision Number: 5.02  
Revision Date: 02/13/2008

9 of  
##NUMPAGES##

Marlex® Polypropylene (All Grades)  
MSDS : 240590